


CM08 Vandalproof Pushbutton

12mm

Ø 14mm

18mm

IP67




Specification


Termination	Solder terminals (2.0 x 0.5mm)
Switching function	Momentary
Configuration of poles	Single
Maximum load	2A, 36VDC
Contact resistance	< 50 mΩ
Insulation resistance	> 1000 MΩ
Operating temperature	-25°C to +55°C
Ingress protection	IP67 (EN 60529)
Duty cycle	200,000 (min)
Operating force	2.5N
Nut mounting torque	2.5Nm
Panel thickness	1.0mm to 7.0mm
Body & button material	See ordering information
Contact material	Silver plated brass

Product Dimensions


Flat



Raised



Front view (all versions)



All dimensions in mm

Engelking


CM08 Vandalproof Pushbutton

Circuit Diagram



Form A

Mounting Dimensions



All dimensions in mm

Ordering information

Material

- V2:** Stainless steel
- AS:** Aluminium black
- BN:** Brass nickel plated

Button

- F:** Flat
- R:** Raised

CM08/ / /M/S/20

Engelking Elektronik GmbH
Albstr. 16 · D-78609 Tuningen · Germany
Tel. +49 (0)7464-9865-0 · Fax +49 (0)7464-9865-71
info@engelking.de · www.engelking.de