


Female panel connector

Product figure (PG9 front fastened solder)

Scale diagram



Contact layout (Front view)

3pins

4pins

5pins

8pins

12pins

17pins

5pins

4pins

A

A

A


A

A

A

B

D



Order Data

Contacts	Coding	Order No
2pins	A	M12A02/FF6/BN/SC
3pins	A	M12A03/FF6/BN/SC
4pins	A	M12A04/FF6/BN/SC
	D	M12D04/FF6/BN/SC
5pins	A	M12A05/FF6/BN/SC
	B	M12B05/FF6/BN/SC
8pins	A	M12A08/FF6/BN/SC
12pins	A	M12A12/FF6/BN/SC
17pins	A	M12A17/FF6/BN/SC

Specifications

Number of contacts	3	4	5	8	12	17
Termination	solder					
Wire gauge	0.14/0.25/0.34/0.5mm ² / (26/24/22/20 AWG)					
Operating temperature	-25°C ~ +80°C					
Mechanical operation	> 100 mating cycles					
Rated voltage	250V		60V		30V	
Rated current (40°C)	4A			2A		1.5A
Protection degree	IP67/IP68					
Contact resistance	< 10mΩ					
Insulation resistance	≥ 100MΩ					
Pin contact	CuZn					
Socket contact	CuSn					
Contact plating	Au					