CM22 19mm Vandalproof Pushbutton

19mm	22mm	17.2mm	IP65
		19.1mm	

Specification

Termination	Screw or 2.8×0.5mm solder terminals
Switching function	Momentary
Configuration of poles	Single
Maximum load	2A, 36VDC
LED voltage	-
Contact resistance	< 50mΩ
Insulation resistance	> 100MΩ
Operating temperature	-25°C to +55°C
Ingress protection	IP65 (EN 60529)
Duty cycle	50,000 (min)
Operating force	4N
Nut mounting torque	~ 0.6Nm
Panel thickness	1.0mm to 6.0mm
Body & button material	See ordering information
Contact material	Silver plated brass

Product Dimensions

All dimensions in mm

Screw Terminals Flat



2.8mm Terminals Flat



Raised



Domed



Front View (all versions)



ENGELKING

Circuit Diagram



Mounting Dimensions



Ordering Information

Material
V2: Stainless steel[1]
AS: Black aluminium

Button
F: Flat
R: Raised
D: Domed

Switch Function
M: Momentary NO
N: Momentary NC

Terminations
20: 2.0mm solder tabs
ST: Screws

CM22 / □ / □ / □ / S / □

[1] 1.4301

Tel: +49 (0)7464 9865 0 Email: info@engelking.de www.engelking.de

ENGELKING