


# CI08 Vandalproof LED

12mm

Ø 15mm

27.4mm

IP67




## Specification


Termination	Fast connect terminals (1.8 x 0.4mm)
LED voltage	See ordering information
Rated current	15mA
Operating temperature	-20°C to +55°C
Ingress protection	IP67 (EN 60529)
Nut mounting torque	5Nm to 14Nm
Panel thickness	1.0mm to 10.0mm
Body material	See ordering information

## Product Dimensions

### Side view



### Front view




Engelking

All dimensions in mm

# CI08 Vandalproof LED

## Mounting Dimensions



All dimensions in mm

## Ordering information

### Material

- V2:** Stainless steel<sup>1</sup>
- BN:** Brass nickel plated

### LED-Colour

- GN:** Green
- RD:** Red
- YL:** Yellow
- BL:** Blue
- WH:** White
- GR:** Green/Red
- BR:** Blue/Red
- GB:** Green/Blue

### LED-Voltage

- 00:** No resistor<sup>2</sup>
- 06:** 6 Volt
- 12:** 12 Volt
- 24:** 24 Volt

CI08/ [ ] /P/D/[ ]/[ ]/18

<sup>1</sup> 1.4301

<sup>2</sup> Green, Yellow: 1.8V Red, Blue, White: 2.8V @20mA

**Engelking**

**Engelking Elektronik GmbH**

Albstr. 16 · D-78609 Tübingen · Germany  
Tel. +49 (0)7464-9865-0 · Fax +49 (0)7464-9865-71  
[info@engelking.de](mailto:info@engelking.de) · [www.engelking.de](http://www.engelking.de)