

# ES08 Vandalproof Pushbutton

19mm

Ø 21.5mm


13.8mm

IP68


## Specification

Termination	15cm flying leads
Switching function	Momentary
Configuration of poles	Single
Maximum load	100mA, 35VDC
Contact resistance	100 mΩ
Insulation resistance	> 10 <sup>9</sup> Ω
Operating temperature	-40°C to +85°C
Ingress protection	IP68 (EN 60529)
Duty cycle	1,000,000 (min)
Operating force	3.6 <sup>+0.7</sup> N
Nut mounting torque	2.5Nm
Panel thickness	0.5 to 8.0mm
Body & button material	See ordering information
Contact material	Gold

## Product Dimensions



## Front view




All dimensions in mm

Engelking


# ES08 Vandalproof Pushbutton

## Circuit Diagram



Form A

## Mounting Dimensions



All dimensions in mm

## Ordering information

### Material

- AN:** Natural anodised aluminium
- A1:** Red anodised aluminium<sup>1</sup>
- A2:** Blue anodised aluminium<sup>1</sup>
- A3:** Yellow anodised aluminium<sup>1</sup>
- A4:** Green anodised aluminium<sup>1</sup>

ES08  F00MML1

<sup>1</sup> Code is only for button material. Housing is made of natural anodised aluminium

**Engelking Elektronik GmbH**  
Albstr. 16 · D-78609 Tuningen · Germany  
Tel. +49 (0)7464-9865-0 · Fax +49 (0)7464-9865-71  
[info@engelking.de](mailto:info@engelking.de) · [www.engelking.de](http://www.engelking.de)